

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-4 (Cancelled)

5. (Currently Amended) An image sensor comprising:

(a) a plurality of light ~~measuring~~ receiving elements a portion of which have a color filter mated with the light receiving elements, and the light receiving elements are arranged in an array;

(b) a plurality of floating diffusions respectively mated with the plurality of light receiving elements;

(c) two column circuits connected to each column of light receiving elements and used to store the signal from the light receiving elements one row at a time; and

(d) a select switch used to control which column circuit a particular signal from a light receiving element is stored, wherein a color difference readout signal is output when a reset signal for at least one column circuit is obtained by sampling the signal of one color and the light signal level for that column circuit is obtained by sampling the signal of a different color.

6. (Curently Amended) The image sensor as in claim 5, wherein substantially all of the signals from the light receiving elements that are in the same column with the same colors are transferred to the same column circuit.

7. (Original) The image sensor as in claim 6, wherein adjacent samples in each column circuit are averaged.

8. (Currently Amended) A camera comprising:

(a) an image sensor comprising:

(a1) a plurality of light ~~measuring~~ receiving elements a portion of which have a color filter mated with the light receiving elements, and the light receiving elements are arranged in an array;

(a2) a plurality of floating diffusions respectively mated with the plurality of light receiving elements;

(a3) two column circuits connected to each column of light receiving elements and used to store the signal from the light receiving elements one row at a time; and

(a4) a select switch used to control which column circuit a particular signal from a light receiving element is stored, wherein a color difference readout signal is output when a reset signal for at least one column circuit is obtained by sampling the signal of one color and the light signal level for that column circuit is obtained by sampling the signal of a different color.

9. (Currently Amended) The camera as in claim 8, wherein substantially all of the signals from light receiving elements in the column with the same colors are transferred to the same column circuit.

10. (Original) The camera as in claim 9, wherein adjacent samples in each column circuit are averaged.

11. (Currently amended) An x-y addressable image sensor comprising:

(a) a plurality of light receiving ~~measuring~~ elements arranged in an array of rows and columns that convert the light to a signal;

(b) at least two signal storage banks comprised of individual signal storage elements; each of the at least two storage banks having enough individual storage elements to store the signals from at least one row of light receiving measuring elements in the array, wherein multiple samples of each signal from at least one row of light receiving elements are concurrently stored in different individual signal storage elements; and

(c) at least two select mechanisms which can direct signals from the plurality of light receiving ~~measuring~~ elements to any single or combination of the signal storage banks.

12. (Currently amended) The image sensor as in claim 11 further comprising a plurality of color filters mated with the plurality of light ~~receiving measuring~~ elements, and the select mechanism is used to send signals from the light ~~receiving measuring~~ elements mated to a single color filter type to a desired signal storage bank such that, for any given row, a single signal storage bank contains signals from a single color type.

13. (Currently amended) The image sensor as in claim 12 wherein the color filter is a Bayer pattern in which signals from a single color type are a color of a single type is sent to only one of the two signal storage banks.

14. (Original) The image sensor as in claim 13, wherein the single color type sent to only one of the storage regions is green.

15. (Original) The image sensor as in claim 11, wherein the individual signal storage elements in the signal storage banks are larger than light measuring element pitch.

16. (Currently amended) The image sensor as in claim 11, wherein the at least two select mechanisms direct signals from the each of the plurality of light ~~receiving measuring~~ elements to both signal storage banks.

17. (Original) The image sensor as in claim 11 further comprising a plurality of signal storage banks and the at least two select mechanisms direct signals to multiple signal storage banks.

18. (Original) The image sensor as in claim 11, wherein a single pixel can be directed to multiple single storage elements within any signal storage bank.

19. (Currently amended) The image sensor of claim 18, wherein adjacent signals from the light receiving ~~measuring~~ elements in the adjacent signal storage elements are averaged to produce a single value.

20. (Original) The image sensor as in claim 11, wherein a single pixel can be directed to adjacent individual signal storage elements within any signal storage bank.

21. (Currently amended) The image sensor of claim 20, wherein adjacent signals from the light receiving ~~measuring~~ elements in the adjacent signal storage elements are averaged to produce a single value.

22. (Currently amended) An image sensor comprising:
(a) a plurality of light receiving ~~measuring~~ elements each having a photodetector and a transfer mechanism; and
(b) a plurality of charge to voltage conversion regions; wherein at least two adjacent light receiving ~~measuring~~ elements share a charge to voltage conversion region;
wherein charge of adjacent light receiving ~~measuring~~ elements is combined in the shared charge to voltage conversion region.

23. (Currently amended) The image sensor as in claim 22, wherein the timing selectively combines charge from light receiving ~~measuring~~ elements with a similar color filter array element.

24. (Currently amended) The image sensor as in claim 22, wherein charge of adjacent light receiving ~~measuring~~ elements is substantially simultaneously transferred to the shared charge to voltage conversion region

25. (Currently amended) The image sensor as in claim 22, wherein the charge of all adjacent light receiving ~~measuring~~ elements associated with a common charge to voltage conversion regions is transferred to the shared charge to voltage conversion region to form a single voltage signal associated with all of the adjacent light receiving ~~measuring~~ elements.

26. (Currently amended) A camera comprising:
an x-y addressable image sensor comprising:
(a) a plurality of light receiving ~~measuring~~ elements arranged in an array of rows and columns that convert the light to a signal;
(b) at least two signal storage banks comprised of individual signal storage elements; each of the at least two storage banks having enough individual storage elements to store the signals from at least one row of light receiving measuring elements in the array, wherein multiple samples of each signal from at least one row of light receiving elements are concurrently stored in different individual signal storage elements; and
(c) at least two select mechanisms which can direct signals from the plurality of light receiving ~~measuring~~ elements to any single or combination of the signal storage banks.

27. (Currently amended) The camera as in claim 26 further comprising a plurality of color filters mated with the plurality of light receiving ~~measuring~~ elements, and the select mechanism is used to send signals from the light receiving ~~measuring~~ elements mated to a single color filter type to a desired signal storage bank such that, for any given row, a single signal storage bank contains signals from a single color type.

28. (Original) The camera as in claim 27 wherein the color filter is a Bayer pattern in which a color of a single type is sent to only one of the two signal storage banks.

29. (Original) The camera as in claim 28, wherein the single color type sent to only one of the storage regions is green.

30. (Original) The camera as in claim 26, wherein the individual signal storage elements in the signal storage banks are larger than light measuring element pitch.

31. (Currently amended) The camera as in claim 26, wherein the at least two select mechanisms direct signals from the each of the plurality of light receiving ~~measuring~~ elements to both signal storage banks.

32. (Original) The camera as in claim 26 further comprising a plurality of signal storage banks and the at least two select mechanisms direct signals to multiple signal storage banks.

33. (Original) The camera as in claim 26, wherein a single pixel can be directed to multiple single storage elements within any signal storage bank.

34. (Currently amended) The camera as in claim 33, wherein adjacent signals from the light receiving ~~measuring~~ elements in the adjacent signal storage elements are averaged to produce a single value.

35. (Original) The camera as in claim 26, wherein a single pixel can be directed to adjacent individual signal storage elements within any signal storage bank.

36. (Currently amended) The camera as in claim 35, wherein adjacent signals from the light receiving ~~measuring~~ elements in the adjacent signal storage elements are averaged to produce a single value.

37. (Currently amended) A camera comprising:
an image sensor comprising:
(a) a plurality of light receiving ~~measuring~~ elements each having a photodetector and a transfer mechanism; and
(b) a plurality of charge to voltage conversion regions; wherein at least two adjacent light receiving ~~measuring~~ elements share a charge to voltage conversion region;
wherein charge of adjacent light receiving ~~measuring~~ elements is combined in the shared charge to voltage conversion region.

38. (Currently amended) The camera as in claim 37, wherein the timing selectively combines charge from light receiving ~~measuring~~ elements with a similar color filter array element.

39. (Currently amended) The camera as in claim 37, wherein charge of adjacent light receiving ~~measuring~~ elements is substantially simultaneously transferred to the shared charge to voltage conversion region

40. (Currently amended) The camera as in claim 37, wherein the charge of all adjacent light receiving ~~measuring~~ elements associated with a common charge to voltage conversion regions is transferred to the shared charge to voltage conversion region to form a single voltage signal associated with all of the adjacent light receiving ~~measuring~~ elements.